

Emission Test Certificate

Tuesday, August 30th, 2016

Supplier: Floor Distributors (PO Box 197 Neutral Bay Junction, NSW 2089)

Sample Description: Urban Laminate Floorboard

Date Tested: August 2016 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D5116 "Standard Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Material/Products".

Emission Data:

Green Building Council of Australia Green Star Interiors V1.1 - 12.1 & 12.2 Green Star Design & As Built V1.1 - 13.1 & 13.2	Urban Laminate Floorboard
Total Volatile Organic Compound Emission Rate limit <0.5 mg/m²/hr	Total Volatile Organic Compound Emission Rate: <0.004 mg/m ² /hr
4-phenylcyclohexene Emission Rate limit <0.05mg/m²/hr	4-phenylcyclohexene Emission Rate: <0.004 mg/m²/hr
Formaldehyde Emission Rate limit <0.1mg/m²/hr	Formaldehyde Emission Rate: 0.011 mg/m²/hr

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Nick Joy BSc(Hons) Consultant Tuan Duong
B. Eng. (Chemical)
Consultant

CV160819